




N A G A R J U N
INTERNATIONAL TRADING COMPANY

We Grow Together...
























AN ISO 9001: 2015 CERTIFIED COMPANY

**INDUSTRIAL WASHING, FINISHING EQUIPMENTS & POWER LAUNDRY MACHINERIES** 

## Manual Utility Pedal Press | Collar & Cuff | Mushroom | Automatic Utility Press



and programmable controls, enabling superior fusing quality.




# Manual Utility Press | Collar & Cuff | Mushroom | Automatic Utility Press


### **PERFOMANCE**


Motor Brand	Specially Designed by us	
Volt	415/3Ø or 220 /1Ø	
Motor Speed Rpm	2880	
Head Movement	Pneumatic Piston	
Table Cloth	Imported Polyster Fabric	
Table Foam	Silicon	<u> </u>
Temperature	0-140°	
Control Panel	By Switches	
Pedal	Limit Switch	
Emergency Switch	Push Button	


#### CONSTRUCTION

Body	Mild Steel		
Table Head	Mild Steel		
Table Bottom	Mild Steel		
Heating Base	Stainless Steel 304 Grade Plate		
Heating Shell	Mild Steel		
Perforated Bottom	Mild Steel		
Perforation	Turret Punch Press		
Pneumatic Piston	Stroke 160mm		
Spring	Helical Expansion		
Side Cover	Mild Steel		
Pedal Base Frame	Mild Steel		
Nuts, Bolts And Connectors	Mild Steel		
Cutting	CNC		
Bending	CNC		
Welding	Laser/MIG/TIG		









Dimensions are in mm

## **AESTHETIC**

Over All Finish	Powder Coated
Logo	Starfish Engraving with LED Lights

#### **TECHNICAL SPECIFICATION**

Mode	SMUPP	SCCP	SMP	SAUP
Pressing Type	Multi Utility	Collar and Cuff	Shoulder & Waist	Multi Utility
Table Size in mm	1067 x 305	1000 x 200	550 x 320	1067 x 305
Suction Area in mm	1067 x 305	1000 x 200	550 x 320	1067 x 305
Live Steam	Available	-	-	Available
Heating Type	Steam	Steam	Steam	Steam
Head Movement	Manually	Automatic	Automatic	Automatic
Over All Dimension	1200 x 1200 x 1400	1200 x 1200 x 1400	1200 x 1200 x 1400	1300 x 1200 x 1400

#### **GENERAL**

Motor Power in kw	0.55	0.55	0.55	0.55
Steam Consumption kg/hour	20	17	15	20
Steam Pressure in mpa	0.4 - 0.6	0.4 - 0.6	0.4 - 0.6	0.4 - 0.6
Air Pressure in mpa	-	0.4 - 0.6	0.4 - 0.6	0.4 - 0.6
Foundation	Not Required			
Net Weight in kg	250	250	220	250

