




N A G A R J U N
INTERNATIONAL TRADING COMPANY

We Grow Together...























AN ISO 9001: 2015 CERTIFIED COMPANY

INDUSTRIAL WASHING, FINISHING EQUIPMENTS & POWER LAUNDRY MACHINERIES

Laundromat | Stack Washer and Dryer

TECHNICAL SPECIFICATION

Model	SLWXD 6	SLWXD 9
DDVED		

DRYER

Dry Weight in Kg	6	9
Drum Size in mm	570 x 460	570 x 460
Door Open in mm	350	350

WASHER EXTRACTOR

Dry Weight in Kg	6	9
Drum Size in mm	468 x 307	481 x 400
Door Open in mm	280	280

GENERAL

DRYER

Motor Power in kw	0.11	0.11
Heating Type	Ele	ctric
Heater in kw	1.75	3.2
Consumption/Hr	1.5 Unit	2 Unit

WASHER EXTRACTOR

Motor Power in kw	0.38	0.45
Heating Type	Elec	ctric
Heater in Kilowatt	1.75	1.75
Dimension in mm	670 x 710 x1800	700 x 740 x 1860
Weight in Kgs	152	162

PERFORMANCE

Motor Brand	Imported	
Volt	220/1Ø	
Forward/Reverse	Adjustable 0-60 Seconds	
Time	0-60 min controlled by PCB	
Control panel	PCB With Feather Touch	
Temperature	0-50° by PCB	
No of Program	3	
Washing Rpm	37	
Extraction Speed	480	
Drying speed Rpm	32	رــــــا

SAFETY

Door Open Cut Off	Limit Switch

CONSTRUCTION	DRYER	WASHER EXTRACTOR
Inner Drum	SS 304 Grade	SS 304 Grade
Outer Drum	-	ABS Plastic
Outer Body	Mild Steel	Mild Steel
Mounting Type	Soft	Soft
Door	ABS Plastic	ABS Plastic
Cutting	CNC	CNC
Bending	CNC	CNC
Welding	Laser/MIG/TIG	Laser/MIG/TIG
Foundation	Not Required	Not Required

AESTHETIC

Overall Finish	Mild Steel with PU Paint
Logo	Starfish Polycarbon Sticker



- Maximize Space Efficiency.
- Stylish design and user-friendly interface.
- Enhanced stability with auto balance technology.
- Rust-resistant stainless steel drum.
- Four wash programs, including a 30-minute quick wash option.
- Temperature selection ranging from cold to 60°, spin speed selection from 0 to 800 rpm.
- Equipped with high-quality SKF bearing for optimal performance under light load conditions.

