




N A G A R J U N
INTERNATIONAL TRADING COMPANY

We Grow Together...























AN ISO 9001: 2015 CERTIFIED COMPANY

INDUSTRIAL WASHING, FINISHING EQUIPMENTS & POWER LAUNDRY MACHINERIES

Washer Extractor | Textile Series





This machine features a Touch screen that allows you to operate it intelligently. You can select from 30 washing programs, including 5 preset ones, to meet your different needs. It can automatically fill water, pre-wash, rinse, bleach and clean your clothes with ease.

The machine is built with high quality stainless steel that can withstand acid, alkali and corrosion. It has a classic look and a long service life. It has a big stainless door with a safety control system. The washer drum is CNC punched with high accuracy and fine workmanship that won't damage your clothes. It also has a unique suspension and anti-shake structure that makes the machine stable and quiet.

The machine uses an imported frequency conversion system that can adjust the drum speed according to the washing and drying needs. It ensures the washing quality and improves the drying efficiency. It also has an imported bearing and oil seal that prevent the drum from leaking or malfunctioning. It has an automatic feeding system that flushes the detergent completely without leaving any residue.









Washer Extractor | Textile Series

PERFORMANCE

PERFORMANCE						
Motor Brand	Imported	Imported	Imported		Imported	
Volt	415 / 3Ø	415 / 3Ø	415 / 3Ø			
Washing speed Rpm	32	32	32			
Medium extract Rpm	400	375	375		350	
High extract Rpm	800	750		700	700	
Forward/Reverse	Adjustable 0-60 Seconds			'		
Water Inlet	Automatic Through Solenoid Valve				1	
VFD	LS/Equivalent					
Washing Time	Adjustable by PCB			$\overline{}$		
Extraction Time	Adjustable by PCB					
Soap Dispensing	Automatic Through Solenoid Valve			<u>-))) </u>		
Water Level	Low/Medium/High					
Control panel	Feather Touch					

SAFETY

Water Drain

No of Programme

Manual Operation

Door Open Cut Off	Limit Switch
Emergency Switch	Yes

Automatic Through Valve

30

Available

CONSTRUCTION

CONSTRUCTION			
Outer Drum	Stainless Steel 304 Grade	Stainless Steel 304 Grade	Stainless Steel 304 Grade
Inner Drum	Stainless Steel 304 Grade	Stainless Steel 304 Grade	Stainless Steel 304 Grade
Perforation	Turret Punch Press	Turret Punch Press	Turret Punch Press
Outer Cover	Stainless Steel 304 Grade	Stainless Steel 304 Grade	Stainless Steel 304 Grade
Back Plate	Mild Steel	Mild Steel	Mild Steel
Mounting Type	Soft	Soft	Soft
Base Frame	Mild Steel Channel	Mild Steel Channel	Mild Steel Channel
Springs	Helical Compression	Helical Compression	Helical Compression
Shock absorber	Heavy Duty	Heavy Duty	Heavy Duty
Doors	Stainless Steel 304 Grade with Pneumatic Lock		
Belt Adjustment	Screw Rod	Screw Rod	Screw Rod
Shaft Gland	Integral Housing With Shaft, Bearing, Oil Seal and Drive System		
Nuts, Bolts And Connectors	Mild Steel	Mild Steel	Mild Steel
Soap Cup	3	5	5
Cutting	CNC	CNC	CNC
Bending	CNC	CNC	CNC
Welding	Laser MIG/TIG	Laser MIG/TIG	Laser MIG/TIG

AESTHETIC

Overal Finish	Matt Finished Stainless Steel
Logo	Starfish Engraving with LED Lights

GENERAL

Motor Power in kw	4	5.5	7.5	
Steam Consumption Kg/Hr	30	50	100	
Water Inlet in mm	32	37	50	
Drain Outlet in mm	90	140	140	
Heater in kw (Optional)	12	18	24	
Door Dimension in mm	420	540	630	
Foundation	Required			
Weight in Kgs	1000	2000	3000	

TECHNICAL SPECIFICATION

Model	SWX 30	SWX 52	SWX 100
Dry Weight in Kg	30	52	100
Drum Size in mm	Ø800 x 590	Ø1060 x 590	Ø1250 x 800
Drum Volume in Liter	300	520	980
Liquor Ratio	1:10		
Over All Dimension in mm	1350 X 1350 X 1750	1500 X 1750 X 1900	1760 X 1950 X 2040

