




N A G A R J U N
INTERNATIONAL TRADING COMPANY

We Grow Together...























AN ISO 9001: 2015 CERTIFIED COMPANY

INDUSTRIAL WASHING, FINISHING EQUIPMENTS & POWER LAUNDRY MACHINERIES

3 in One Washer, Extractor and Dryer



Mechanism Of Action: Our all in one washer, extractor and dryer is a versatile and efficient laundry solution that performs washing, extracting and drying functions in the same machine. It is also known as industrial washer cum dryer.

- Blue LCD screen with dialogue interface of human operation being able to realize Intellectualized operation: automatically pouring water, pre-washing, rinsing, bleaching and cleaning.
- Microprocessor, freely programmable, with 5 types of washing programs available. Easy operating.
- Adopt high quality stainless steel, acid and alkali resistance, anti-corrosion, classical appearance, long life.
- Automatic feeding system, aerodynamic design, flushes the material completely, without residual.
- Unique structure of suspension and shake proof, greatly improves the stability of the machines, low noise.
- The imported precise and durable bearing and framework oil seal assure the liability of drum precision and air proof, no leakage, so the rate of troubles is greatly reduced.
- High Quality Electric Heater ensures quick drying time.

PERFORMANCE

PERFORMANCE				
Motor Brand	Imported	Imported		
Volt	415 / 3Ø or 220 / 1Ø			
Washing speed Rpm	37			
Medium extract Rpm	400			
High Extract Rpm	650	800	800	
Forward/Reverse	Adjustable 0-60	Seconds		
Water Inlet	Automatic Through Solenoid Valve			
VFD	LS/Equivalent			
Washing Time	Adjustable by PCB			
Extraction Time	Adjustable by PCB			
Soap Dispensing	Automatic Through Solenoid Valve			
Water Level	Low/Medium/High			
Control panel	Feather Touch			
Water Drain	Automatic Through Valve			
No of Programme	5			
Manual Operation	Available			
SAFETY	1			
Door open cut off	Limit Switch			
Emergency Switch	Yes			
Construction				
Outer Drum	Mild Steel			
Inner Drum	Stainless Steel 304 Grade			
Perforation	Turret Punch Press			
Outer Cover	Stainless Steel 304 Grade			
Back Cover	Galvanized Iron			
Mounting Type	Hard Soft			
Base Frame	Mild Steel Channel			
Springs	Helical Compression			
Shock absorber	Light Duty			
Doors	Stainless Steel 304 Grade with Double Lock			
Belt Adjustment	Screw Rod			
Shaft Gland	Housing With Shaft, Bearing & Oil Seal			
Nuts, Bolts	Mild Steel			
Soap Cup	2			
Cutting	CNC			
Bending	CNC			
Welding	LaserMIG/TIG			
AESTHETIC				
Overall Finish	Matt Finished Stainless Steel			
Logo	Starfish Engraving with LED Lights			
TECHNICAL SPECIFICA	TION			
Model	SWXD 10	SWXD 15	SWXD 20	
Washing in Kg	10	15	20	
Drying in Kg	5	7.5	10	
Drum Size in mm	Ø630 x 320	Ø670 x 430	Ø730 x 430	
Drum Volume in Ltr	100	152	200	
Liquor Ratio	1:10	1:10	1:10	
Dimension in mm	850 x 900 x 1500	1000 x 1100 x 1600	1000 x 1100 x 1600	
GENERAL	I			
Motor Power in kw	1.5	1.5	2.25	
Water Inlet in mm	15	18	20	
Drain Outlet in mm	50			
Heater in kw Optional	6	6	6	
Foundation	Required			
Weight in Kgs	500	600	700	
Heating Type	Electric			
Heater in Kilowatt	4	6	8	
Consumption/Hr	3 Unit	4.5 Unit	6 Unit	



